



## **Honda TRX 450 Duals INSTALLATION INSTRUCTIONS**

### **PLEASE READ INSTRUCTIONS BEFORE ATTEMPTING INSTALLATION**

Remove stock slip-on and header. Remove rear plastic. Remove stock air box and snorkel. Unbolt your stock regulator from the left side of the frame. This bracket that is welded to the frame needs to be removed. (This process is easily done with a disc cutter). The regulator will re-mount to the air box mounting tabs.

### **JETTING**

Rotate the carburetor clockwise (when sitting on the ATV) remove the hex nut on the bottom of the float bowl. Replace the stock main jet with the supplied (185) main jet. Replace the hex nut and re-mount the carburetor to the manifold.

### **EXHAUST MOUNTING**

Mount the "Y" manifold to the cylinder leaving the nuts a little loose so you can rotate for best fit. Slide both clamps over the ends of the manifold.

Install the right pipe from the rear of the ATV between the shock and the frame and slip it over the manifold. Attach the bracket on the inside of the fender and the heel guard brackets. Mount to this location with the supplied 6 x 25 mm bolt, flat and lock washer. Spray a little WD-40 on the end of the chamber, slide the right hand silencer into the chamber. Mount the silencer bracket to the rear fender support bracket with the supplied 6 x 40 mm bolt, flat and lock washer. (Leave hardware off of silencer bracket until you mount the other pipe and re-install your plastic).

Before you mount the left pipe you need to remove the chain guard temporarily for installation. Slide the left chamber in from the rear of the frame and slide it over the manifold, pull the rear of the chamber through the frame and mount to the upper hole behind the heel guard support bracket with the supplied 6 x 25 mm bolt, flat and lock washer. Install the silencer in the same manor as the right side leaving the hardware off the bracket.

Re-install the air box and snorkel. Mount the regulator on the outside of the left side mounting bracket with supplied 6 x 25 mm bolt, flat and lock washer.

Re-install your rear plastic as it was removed. Use the supplied hardware to mount the silencers to the rear fender bracket.

Tighten the cylinder nuts, then the t-bolt clamp, and then the rear frame brackets. Re-install your chain guard. The cluster of wires and cables that run from the left side of the cylinder up to the radiator need to be pulled down a little and attached to the electric fan housing with the supplied zip tie. (Be sure the zip tie does not restrict the fan movement).

Remove you air box lid, and check that no wires or hoses are touching the pipe. (If they are zip tie the back).

## **QUIET CORES**

Quiet cores are supplied with this kit but not installed. To install the quiet cores remove both rear end caps ((turn downs) and install the quiet cores with the tubes facing inward. Re-install the end caps.

## **FIRST RIDE**

Your first ride should be for 20 to 30 minutes, then turn bike off to let cool. Re-torque all hardware on your new exhaust from your cylinder to the silencers.

## **Silencer Packing**

We recommend checking you're packing every 15 to 20 hours of riding. As your decibel level will increase and without the packing will damage the internals of your silencers. No Warranty will be given for failure from lack of maintaining.

**IMPORTANT MESSAGE—PLEASE READ AND UNDERSTAND!**  
**WARRANTY LIMITATIONS**

**Looney Tuned Exhaust (LTE) warrants only to the original purchaser the equipment purchased is free from defects in material and workmanship under normal use and service.** Components of the equipment are supplied to LTE by others and LTE warrants such components to the purchaser only to the extent that such components are warranted to LTE by the supplier. LTE's obligation under this warranty shall be limited to the repair or exchange of any part or parts which may thus prove defective under normal use and service within one year from date of invoice and which LTE examination shall disclose to LTE's satisfaction to be thus defective. This warranty is expressly in lieu of all other warranties expressed or implied and of all other obligations or liabilities on our part and LE neither assumes, nor authorizes any other person to assume for LTE any other liability in connection with the sale of this equipment or any part thereof which has been subject to accident, negligence alteration, abuse or misuse. LTE makes no warranty what so ever in respect to accessories or parts not supplied by LTE. The term "original purchase", as used in this warranty, shall be deemed to mean that person for whom the equipment is originally invoiced. This warrant shall apply only within the boundaries of the continental United States.

The remedy defined in this statement shall be the Purchaser's exclusive remedy against Looney Tuned Exhaust (LTE).

In no case shall Looney Tuned Exhaust (LTE) be liable hereunder for any consequential Damages.

**THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, WHICH EXTEND BEYOND THE FACE OF THIS STATEMENT.**

**Please be sure that no hoses**  
**or wiring will vibrate or lay**  
**against the exhaust before**  
**you take off for your first**  
**ride!!!!**

**AND**

**Don't forget to check your**  
**silencer packing!!!!!!**